







### Comfortable, Compact and HSE compliant.

The **groundhog** mobile GP360D is a lightweight and compact towable unit that meets HSE & CDM requirements and provides all your on-site needs in one small package.

The units are suitable for accommodating six people, which provides pleasant and safe working environments, ideal for rental companies and contractors.

Easily towed, one man operation secured and manoeuvred on site, in less than 3 minutes. Its many safety features make it a **high secure and money saving choice of welfare unit**.

## INNOVATION THAT WORKS.

Recycled non-slip



Warm water from an on-board heating system



Welded boss for

lifting eyes

Fully hot-dipped galvanised chassis



240V LED 600mm strip light



Fuel Active system



230V 1kW air blown heater



230V single 2Amp socket



Lowered & secured in 3 minutes

## **KEY FEATURES** at a glance

Length	<b>3655</b> mm
Length (including drawbar)	<b>4920</b> mm
Height (on wheels)	<b>2.9</b> m
Height (on ground)	<b>2.5</b> m

Generator	
Unladen Weight	<b>1700</b> kg
Possible Gross Weight	<b>1800</b> kg*
Solar Panel	

Fresh Water	20 Litres
Waste Water	20 Litres
Toilet Tank Size	280 Litres
Fuel Tank Size	58 Litres



1 Canteen Area
Table and bench seating for up to 6 people
240V 600mm strip light
230V 1kW air blown heater
Warm water supplied by on-board heating system
Large stainless steel sink c/w warm water tap
230V single 2Amp socket outlet
Generator start panel c/w hour run meter
Fresh & waste water containers (20 Ltr cap each)
12V pump for water system
Carbon monoxide monitor and smoke alarm

		-	
	Tai	lot A	roa
_	101	е А	lea

\* Fully laden gross weight exceeds maximum towing capacity, unit should be transported to site prior to making site ready.

Plastic recirculating toilet

12V LED lighting with PIR

Forearm wash basin c/w warm water tap

Warm water supplied by on-board heating system

#### 3 Generator/Warm Room

Bulkhead light 240V

240V tubular heater

Access to fuel tank with separate fuel level gauge (58 Ltr cap)

Ventilation panel

Fuel Active system

Fuel tank runtime = approx. 25 hours

# Secured in less than 3 minutes

#### Easily towed, one man operation secured and manoeuvred on site.

Fast deployment time means more time on the job, making it the money saving choice of welfare unit for rental companies and contractors.






Unhitch from towing vehicle and operate hydraulics using the push button controls



Lower unit to the ground and unplug controls



Close & lock canopy to protect towing facility



For more information on the **Vinco Sales Ltd** GP360D or to discuss your requirements please visit our website to find your local branch.

# vincosales.co.uk

#### Vinco Sales Ltd

The Kivernoll Building Much Dewchurch Hereford Herefordshire HR2 8DU

01981 540 899

info@vincosales.co.uk

PORTABLE BUILDINGS, CONTAINERS & WELFARE SOLUTIONS



Manufactured by Groundhog.

Reduction savings shown are based on a correctly serviced operational unit. Groundhog reserve the right to change specification without prior notice.

Version 1.1 09/23 Copyright ©2019 Groundhog UK Limited. All rights reserved. No part of this material may be reproduced in any form by any means without the express written permission of Groundhog UK Limited